

weberprim TG5

Acrylic dispersion based, one component adherence primer

Technical Data Sheet:
Issued on 12.08.2024
Revision No: 004

Description

Acrylic dispersion based, one component adherence primer.

Advantages

- One component ready to use.
- Supporting substrate strength in tile applications on tile.
- Feature of protecting wood floors from humidity of tile adhesive.

Range of application

- Used as primer for the purpose of improving surface adherence before tile adhesive in all renovations.

Application substrates

- Interior and exterior wall;
- All types of tiles,
- Painted substrates (acrylic or alkyd-based).
- Interior and exterior floor;
- All types of tiles,
- Hard vinyl flooring,
- Wooden substrates,
- Metal substrates,
- Please consult us for all other application substrates.

Preparation of substrates

- The substrate should be clean, dry and smooth.
- The substrate should be cleaned out plaster, paint, glue, oil, cement residuals completely.
- The substrate should be washed with water and left to dry.
- Lacquer, beeswax and similar residuals on wooden and parquet substrates should be cleaned by scraping and even with scraper. The substrate should be free from dust

Conditions of application

- The ambient temperature: +5 °C and +35 °C.
- Avoid application in very hot and/or very damp weather.
- The substrate should be completely dry.

Application

- **weberprim TG 5** should be mixed until homogenous state is achieved without diluting.
- **weberprim TG 5** should be applied on the whole substrate with lambskin roller and brush in equal and single thickness.
- **weberprim TG 5** should be the time required for the application of ceramics on it min. 4 hours.

Application tools

Lambskin roller, brush, trowel.

Consumption

weberprim TG 5	100-110 ml/m ²
-----------------------	---------------------------

Attention Points

- Gypsum paster is not applied on plaster board and gypsum block
- Does not apply on constantly wet and damp surfaces.
- In order to main the surface adherence that **weberprim TG 5** will provide, care should be taken not to get dirty during application.
- Absolutely no foreign materials should be taken
- Contact with the skin should be avoided and gloves should be used during application.
- After application, all tools should be washed with water before drying.

Storage

Packaging	<ul style="list-style-type: none">• Net 4,2 lt (5 kg) bucket.• Net 0,85 lt (1 kg) bucket (5 buckets in one box),/Pink
Shelf life	<ul style="list-style-type: none">• 1 year as of the production date in dry and moisture- free environment provided that packages will not be opened.• Package should be kept tightly closed when not in use. Package should be protected against frost.

Safety Precautions

- Use the appropriate safety equipment (dust mask, gloves).
- Protect your eyes / face.
- Avoid contact with eyes and skin.
- In case of contact with eyes, rinse immediately with plenty of water and consult a specialist.
- Read the Material Safety Data Sheet for more detailed

Legal Warning

Since there are different conditions and requirements that apply in any case, Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş. cannot be liable for other than the information provided in this product datasheet.

Access detailed documentation of the product by scanning QR or tr.weber



The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures. Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.

Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.tr.weber • info@tr.weber • Çözüm Hattı 444 6 990

 **weber**
SAINT-GOBAIN